How to Order HUCKCOMP® (LGP®) Stump-Type Lockbolts EXAMPLE: HLGPS9SC-V08B06AC

H LGPS 9SC - V 08 B 06 AC

Finish Codes
No Suffix = Uncoated Pin Plus Cetyl Alcohol Lube
AC = Aluminum Coat Plus Cetyl Alcohol Lube with Black Color on Stump End
AD = Aluminum Coat Plus Cetyl Alcohol Lube with White Color on Stump End
AS = Anodize "Blue" Plus Cetyl Alcohol Lube
B = Uncoated Pin and No Lube
EP = Phosphate Fluoride
EPR = Phosphate Fluoride Plus Cetyl Alcohol Lube with Red Color on Stump End
PB = Powdered Blast Top Surface of Head Plus Cetyl Alcohol Lube

Grip Length
1/16" Increments

Miscellaneous
B = Standard Composite Installation Loads

Shank Diameter
1/32" Increments

Material Code
V = 6AL-4V Titanium

Head Configuration
7SC = 100° Shear/Tension (MS20426) Flush Head (composite application)
8SC = 100° Tension (MS24694) Flush Head (composite application)
9SC = 130° Shear Crown Flush Head (composite application)
9SP = Shear Protruding Head (composite application)
12SP = Tension Protruding Head (composite application)

Family
Lightweight Groove Proportioned (Stump-Type)

Sealant Escape Groove
H = Sealant Escape Groove Option

HUCKCOMP and LGP are trademarks of Howmet Aerospace Inc. or one of its subsidiaries.
© 2020 Howmet Aerospace Inc.